

## Terminal Tractor/Yard Spotter

Used Yard Spotter New Mexico - Tow tractors, sometimes call towing tractors or tow tugs, are vehicles used in transporting loads horizontally in warehouses, manufacturing plants, airports, arenas and other large facilities. Tow tractors are responsible for moving multiple trailers in a train. Tow tractors can move aircraft into and outside of airport locations such as terminals and hangars. Tractive effort is how these machines transport loads. Tractive effort is the amount of traction a unit has on the ground. The heavier the load is, the more tractive effort is needed. The tow tractor lifts a portion of the load during towing while ensuring the wheels on the load still remain on the ground. The load is partially lifted by use of the tow tractor's hydraulic mast which is specifically designed to produce downforce on the drive wheel immediately beneath it, increasing the tractive effort. The tow tractor is capable of transporting very heavy and large loads thanks to the traction it provides.

**Types of Tow Tractors** There are two basic types of tow tractors: 1. Load carriers; and 2. Heavy-duty tow tractors; Load Carriers Industries such as e-commerce, manufacturing, and airport baggage and parcel systems must regularly move many individual and varying sized items to or from a single location. Tow tugs or load carrier tow tractors are excellent for these jobs as they can maneuver single items stacked on wheeled platforms for streamlined transport. The category that load carrier tow tractor models fall into includes forklift trucks, cranes and pallet jacks. These units only transport loads at ground level and do not lift or lower items from shelving or off the ground. This means that the load has already been on wheels or placed on a wheeled platform before transport. The wheeled platforms are called bogies, trollies or skates. The tow tug is attached to the trolley similar to train cars being attached to a locomotive. Generally, the steel coupling on the tow tug's male-end joins to the front trolley's female-end. The back of the trolley has a male-end steel coupling that can then be used to attach multiple trollies onto a single tow tug, transporting all the trollies in a train-like formation. Tow tractors with a train of trollies enable a wider range in the type of items that can be transported and in the types of conditions they can be transported. Trolley types differ to provide customization options. Many trollies can be connected since they are compatible with one another. Different kinds of trollies can be maneuvered in a single train, creating flexible transport options. Load carrier tow tractors deliver a clear view for the operator which can be better than relying on forklifts. Load carrier tow tractors transport trollies in a forward direction which decreases the safety concerns common with reverse forklift operations. This is vital for safety-sensitive places including airports and manufacturing facilities. It is more economical to tow multiple items when possible with a tug than using a forklift truck to transport single items. Tugs are simple to move and provide a safe transport option. A key benefit of these units is that typically, the operator doesn't need a license. No license is necessary since these units do not lift loads up from the ground like cranes, and forklifts that require licensing. There are three subtypes of load carrier tow tractors: 1. Pedestrian; 2. Stand-in; and 3. Rider-seated.

**Pedestrian Tow Tractors** Pedestrian tow tractors go by many names including electric tow tractor, electric tug, or electric tugger. These units are walk-behind models that move wheeled loads. These machines are simple to use, extremely maneuverable and very compact.

**Stand-in Tow Tractors** Stand-in tow tractors are the most popular design for industries that involve order picking and horizontal transport in manufacturing. Stand-in tow tractors feature a tinier footprint compared to rider-seated editions and they offer a safe driver platform.

**Rider-Seated Tow Tractors** Similar to stand-in tow tractors, rider-seated units have a seated operator platform. These models are commonly used for transporting loads over farther distances such as moving checked baggage from the airport check-in to the aircraft at the terminal. Reducing rider fatigue, the rider-seated models deliver more efficiency.

**Heavy Duty Tow Tractors** In the aviation industry, large passenger and cargo planes usually employ the concept of pushback. Pushback is the process of pushing an aircraft back from the terminal by means not originating from the aircraft's personal power. Heavy-duty tow tractors are known as pushback tugs or pushback tractors complete this task. Pushback tractors are designed with a

low profile design to enable them to move under the aircraft's nose in order to attach to the aircraft. Enough ground friction is required to move the weighted aircraft, so these models need to be heavy themselves. A common tractor for moving large aircraft can weigh in up to fifty-four tons. Their driver's cab has the ability to be lowered and raised for increased visibility during reversing. The pushback tow tractor and pushback tug are also employed when taxiing the aircraft is not an option. They are commonly used to move the machine into and outside of aircraft maintenance hangars. The two subtypes of pushback tow tractors include conventional tow tractors and towbarless tow tractors.

### Conventional Pushback Tow Tractors

Conventional units rely on a tow bar to connect the tug to the aircraft's nose landing gear. The tow bar is laterally fixed at the nose landing gear; however, it is possible to make height adjustments with slight vertical movements. At the end that attaches to the tug, the tow bar may pivot freely laterally and vertically. Acting like a giant lever, the tow bar can rotate the nose landing gear. Every aircraft has a special tow fitting and the towbar functions as an adapter between the fitting on the landing gear and the standard-sized tow pin. Heavy-duty towbars required for sizeable aircraft ride on their own wheels when they are disconnected from the machine. The wheels are attached to a hydraulic jacking mechanism which can lift the towbar to the correct height to mate to both the airplane and the tug, and once this is accomplished the same mechanism is used in reverse to raise the tow bar wheels from the ground during the pushback process. The towbar is capable of being connected at the tractor's rear or front, depending on if the machine needs to be pulled or pushed. Depending on whether the aircraft needs to be pushed or pulled, the towbar can be attached to the front or rear of the tractor.

### Towbarless Pushback Tow Tractors

Towbarless tractors work without a towbar and scoop up the aircraft's nose landing gear to lift it off of the ground instead. This offers better control and higher speeds while eliminating the requirement of having a worker stationed in the cockpit to put the brakes on. Simplicity is the main advantage of the towbarless tugs since it is not necessary to maintain a variety of towbars. Greater control and responsiveness while moving the aircraft is achieved with this direct connection of the tug to the landing gear.